



Product technical sheet

CLIMBOO WD1420







3 - 14 years

18 kids

31,8 m²



Material specification

- Construction made of the highest quality laminated, impregnated and double coated pine wood 90 x 90 mm without knots, secured from the top with polypropylene plugs,
- Metal anchors made of hot dip galvanized steel, protecting the wood from direct contact with the ground to prevent rot and to extend the product's life,
- Platforms and climbing walls made of durable anti-slip and waterproof plywood or HPL plate
- Climbing walls made of durable anti-slip and waterproof plywood or HPL plate,
- Climbing stones made of durable HDPE plate, resistant to weather conditions,
- Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,
- Ladders made of steel ropes in polypropylene braid and rungs made of synthetic material,
- Calibrated stainless steel chains, preventing fingers entrapment,
- Stainless steel bars and handrails,
- Stainless steel screws and/or screws covered with plastic caps,
- Safe end caps made of polypropylene,



Physical development



pull-up climbing




passage


Vinci Group Sp. z o.o. Seminaryjna 9 Street 99-400 Łowicz VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991














Product technical sheet

CLIMBOO WD1420

Product data

Length	290 cm	
Width	255 cm	
Total height	200 cm	
Age group	3 - 14 years	
Number of users	18 kids	
Safety zone	31,8 m2	
Free fall height	190 cm	
In accordance with norm EN	1176-1:2017	
Weight of the heaviest part	13 kg	
Dimensions of the largest part	265x9x9 cm	
Availability of spare parts	YES	
Installation time	5 h	
Color options		

Data is subject to change without prior notice.

Additional information

- equipment intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- render is for reference only, the actual appearance of the equipment and its color may vary;

Guarantee



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card



VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26

M: +48 793 404 991





Surfaces according to EN 1176-1:2017

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
hark (A (1)	Particle size from 20	30	≤200
	to 80	40	≤300
woodchips (A,C)	Particle size from 5 to 30	30	≤200
		40	≤300
sand or gravel (A,C)	Particle size from 0,25 to 8	30	≤200
		40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		190

Product technical sheet

CLIMBOO WD1420

Amount of safe surface corresponding with free fall height:

HIC 190 31,8 m²

Data is subject to change without prior notice.

