



### **Product technical sheet**

# **MINISWEET 0103**







1 - 8 years

14 kids

23,2 m<sup>2</sup>



### **Material specification**

- Stainless steel, hot-dip galvanized and powder coated or powder galvanized and powder coated steel construction of 80 x 80 mm profile,
- Balconies of hot-dip galvanized and powder coated steel,
- Platforms made of durable anti-slip and waterproof plywood or HPL plate,
- Roofs, side panels made of durable HDPE or HPL plate, resistant to weather conditions,
- Educational paneles and moving elements made of HDPE or HPL plate, resistant to weather conditions,
- Double wall tube passage made of polypropylene,
- Screws covered with plastic caps and/or stainless steel screws,
- Safe end caps on top of the structure made of rubber or polypropylene,



### **Facilitating disability**



easy access



shelters







#### Intellectual development



manipulation

thinking



sight



### Physical development



hiding



crawling









## **Product technical sheet**

## **MINISWEET 0103**


#### **Product data**


Length	255 cm	
Width	240 cm	
Total height	170 cm	
Age group	1 - 8 years	
Number of users	14 kids	
Safety zone	23,2 m2	
Free fall height	<60 cm	
The height of the platforms	12 cm	
In accordance with norm EN	1176-1:2017	
Weight of the heaviest part	14 kg	
Dimensions of the largest part	179x8x8 cm	
Availability of spare parts	YES	
Installation time	5 h	
Color options	60000	


Data is subject to change without prior notice.

#### **Additional information**

- equipment adapted for the disabled; intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- render is for reference only, the actual appearance of the equipment and its color may vary;







## Guarantee



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card



VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991





## Surfaces according to EN 1176-1:2017

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A.C.)	Particle size from 20	30	≤200
bark (A,C)	to 80	40	≤300
adahina (A.C.)	Particle size from 5	30	≤200
woodchips (A,C) to 30	to 30	40	≤300
sand or gravel (A,C)  Particle size from 0,25 to 8	Particle size from	30	≤200
	0,25 to 8	40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		60

## **Product technical sheet**

# **MINISWEET 0103**

Amount of safe surface corresponding with free fall height:

HIC <60 23,2 m<sup>2</sup>

Data is subject to change without prior notice.

