

# RECYCLED RC1552



1 - 8 years



10 kids



19,9 m²



## Material specification

- The structure is made of a durable, moisture-resistant and low-temperature recycled composite,
- Platforms made of durable anti-slip and waterproof plywood or HPL plate,
- Structure for platforms made of hot-dip galvanized and powder coated steel;
- Roofs and side panels made of recycled HDPE plates, resistant to weather conditions, green HDPE panels made of 100% recycled materials, e.g. ocean waste such as fishing nets and ropes
- Educational panels made of recycled HDPE plates, resistant to weather conditions, green HDPE panels made of 100% recycled, e.g. ocean waste such as fishing nets and ropes,
- Stainless steel bars,
- Screws covered with plastic caps and/or stainless steel screws,
- Safe end caps made of polypropylene,



### Facilitating disability



for visually impaired



easy access



shelters



integration



### Intellectual development



manipulation



thinking



### Physical development



hiding



rest





**2**  
number of  
towers



**2**  
number of  
roofs



**7**  
number of interactive  
elements

## Product technical sheet

# RECYCLED RC1552




## Product data

|                                |             |
|--------------------------------|-------------|
| Length                         | 244 cm      |
| Width                          | 100 cm      |
| Total height                   | 184 cm      |
| Age group                      | 1 - 8 years |
| Number of users                | 10 kids     |
| Safety zone                    | 19,9 m2     |
| Free fall height               | <60 cm      |
| The height of the platforms    | 35 cm       |
| In accordance with norm EN     | 1176-1:2017 |
| Weight of the heaviest part    | 8 kg        |
| Dimensions of the largest part | 159x9x9 cm  |
| Availability of spare parts    | YES         |
| Installation time              | 4 h         |

Data is subject to change without prior notice.

## Additional information

- equipment adapted for the disabled; intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimmie the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- slide should not be installed southwards;
- render is for reference only, the actual appearance of the equipment and its color may vary;



## Guarantee

**30**

30 year guarantee -  
Structural strength of steel  
and stainless steel  
components

**15**

15 year guarantee -  
Structural failure of steel  
and stainless steel, for  
dynamic equipment

**10**

10 year guarantee - Structural  
failure of high density  
polyethylene and high  
pressure laminates  
components

**5**

5 year guarantee - Corrosion of stainless  
steel and hot dip galvanized and powder  
coated components; against bark beetles  
and rot in case of wooden structural  
elements

Detailed information in the guarantee card

**Vinci Group Sp. z o.o.**  
Seminarnyja 9 Street  
99-400 Łowicz

VAT: 534-250-14-46  
PHONE: +48 42 203 24 99 ext. 26  
M: +48 793 404 991



biuro@vinci-play.com  
info@vinci-play.com  
[www.vinci-play.com](http://www.vinci-play.com)

## Surfaces according to EN 1176-1:2017

|                                 | Description (mm)             | Layer thickness (cm) | Maximum fall heights (cm) |
|---------------------------------|------------------------------|----------------------|---------------------------|
| Turf/ top layer of soil (A,B,C) | -                            | -                    | ≤100                      |
| bark (A,C)                      | Particle size from 20 to 80  | 30                   | ≤200                      |
|                                 |                              | 40                   | ≤300                      |
| woodchips (A,C)                 | Particle size from 5 to 30   | 30                   | ≤200                      |
|                                 |                              | 40                   | ≤300                      |
| sand or gravel (A,C)            | Particle size from 0,25 to 8 | 30                   | ≤200                      |
|                                 |                              | 40                   | ≤300                      |
| synthetic attested (A,B,C)      | Tested according to EN 1177  |                      | 60                        |

## Product technical sheet

# RECYCLED RC1552

### Amount of safe surface corresponding with free fall height:

HIC <60 19,9 m<sup>2</sup>

Data is subject to change without prior notice.

