



Product technical sheet

SOLO WD1468







1 - 8 years

years 1

1 kids

10,1 m²

Material specification

- Construction made of the highest quality laminated, impregnated and double coated pine wood 90 x 90 mm without knots, secured from the top with polypropylene plugs.
- Metal anchors made of hot dip galvanized steel, protecting the wood from direct contact with the ground to prevent rot and to extend the product's life,
- Moving elements made of durable HDPE or HPL plate, resistant to weather conditions,
- Screws covered with plastic caps and/or stainless steel screws,



Facilitating disability



easy access



integration



Intellectual development




manipulation





thinking











Product technical sheet

SOLO WD1468

Product data

| Length | 84 cm | |
|--------------------------------|-------------|--|
| Width | 12 cm | |
| Total height | 130 cm | |
| Age group | 1 - 8 years | |
| Number of users | 1 kids | |
| Safety zone | 10,1 m2 | |
| Free fall height | <60 cm | |
| In accordance with norm EN | 1176-1:2017 | |
| Weight of the heaviest part | 9 kg | |
| Dimensions of the largest part | 120x9x9 cm | |
| Availability of spare parts | YES | |
| Installation time | 1 h | |
| Color options | | |

Data is subject to change without prior notice.

Additional information

- equipment adapted for the disabled; intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- render is for reference only, the actual appearance of the equipment and its color may vary;

Guarantee



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card



VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991





Surfaces according to EN 1176-1:2017

| | Description (mm) | Layer thickness (cm) | Maximum fall heights (cm) |
|---|---------------------------------|-------------------------|------------------------------|
| Turf/ top layer of soil (A,B,C) | - | - | ≤100 |
| bark (A,C) Particle size from 20 to 80 | 30 | ≤200 | |
| | to 80 | 40 | ≤300 |
| woodchips (A,C) | Particle size from 5 | 30 | ≤200 |
| | to 30 | 40 | ≤300 |
| sand or gravel (A,C) | Particle size from 0,25 to 8 | 30 | ≤200 |
| | | 40 | ≤300 |
| synthetic attested (A,B,C) | Tested according to EN 1177 | | 60 |

Product technical sheet

SOLO WD1468

Amount of safe surface corresponding with free fall height:

HIC <60 10,1 m²

Data is subject to change without prior notice.

