

# STEEL+ 1708



3 - 14 years



24 kids



40,5 m<sup>2</sup>



## Material specification

- Powder galvanized and powder coated or stainless steel construction of 80 x 80 mm profile,
- Platforms and climbing walls made of durable anti-slip and waterproof HPL plate,
- Roofs and side panels made of durable HDPE plate, resistant to weather conditions,
- Slides made of stainless steel with durable HDPE side panels,
- Fireman's pole made of stainless steel,
- Drawing board made of durable HPL plate, resistant to weather conditions,
- Music panels made of durable HPL plate, resistant to weather conditions,
- Telescope made of stainless steel and durable HDPE plate, resistant to weather conditions,
- Rudder made of durable HDPE plate, resistant to weather conditions,
- Durable climbing stones made of polyester resin composite with mineral fillers,
- Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,
- Ladders made of steel ropes in polypropylene braid and rungs made of synthetic material,
- Calibrated stainless steel chains, preventing fingers entrapment,
- Stainless steel bars and handrails,
- Screws covered with plastic caps and/or stainless steel screws,
- Safe end caps on top of the structure made of rubber or polypropylene,



### Facilitating disability



easy access



integration



### Intellectual development



manipulation



music



sight



thinking



### Physical development



pull-up



passage



climbing





**2**

number of towers



**1**

number of slides



**2**

number of roofs





**5**

number of interactive elements



**8**

number of activity elements



## Product technical sheet

# STEEL+ 1708

## Product data

|                                |                     |
|--------------------------------|---------------------|
| Length                         | 400 cm              |
| Width                          | 356 cm              |
| Total height                   | 373 cm              |
| Age group                      | 3 - 14 years        |
| Number of users                | 24 kids             |
| Safety zone                    | 40,5 m <sup>2</sup> |
| Free fall height               | 220 cm              |
| The height of the platforms    | 150, 180 cm         |
| slide platform height          | 150 cm              |
| In accordance with norm EN     | 1176-1:2017         |
| Weight of the heaviest part    | 35 kg               |
| Dimensions of the largest part | 396x8x8 cm          |
| Availability of spare parts    | YES                 |
| Installation time              | 7,0 h               |

Color options



Data is subject to change without prior notice.

## Additional information

- equipment adapted for the disabled; intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimmie the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- slide should not be installed southwards;
- render is for reference only, the actual appearance of the equipment and its color may vary;

## Guarantee

**30**

30 year guarantee - Structural strength of steel and stainless steel components

**15**

15 year guarantee - Structural failure of steel and stainless steel, for dynamic equipment

**10**

10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components

**5**

5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card

**Vinci Group Sp. z o.o.**  
Seminarnyja 9 Street  
99-400 Łowicz

VAT: 534-250-14-46  
PHONE: +48 42 203 24 99 ext. 26  
M: +48 793 404 991

01/12/2022



biuro@vinci-play.com  
info@vinci-play.com  
[www.vinci-play.com](http://www.vinci-play.com)

## Surfaces according to EN 1176-1:2017

|                                 | Description (mm)             | Layer thickness (cm) | Maximum fall heights (cm) |
|---------------------------------|------------------------------|----------------------|---------------------------|
| Turf/ top layer of soil (A,B,C) | -                            | -                    | ≤100                      |
| bark (A,C)                      | Particle size from 20 to 80  | 30                   | ≤200                      |
|                                 |                              | 40                   | ≤300                      |
| woodchips (A,C)                 | Particle size from 5 to 30   | 30                   | ≤200                      |
|                                 |                              | 40                   | ≤300                      |
| sand or gravel (A,C)            | Particle size from 0,25 to 8 | 30                   | ≤200                      |
|                                 |                              | 40                   | ≤300                      |
| synthetic attested (A,B,C)      | Tested according to EN 1177  |                      | 220                       |

## Product technical sheet

# STEEL+ 1708

### Amount of safe surface corresponding with free fall height:

|         |                     |
|---------|---------------------|
| HIC 100 | 4,4 m <sup>2</sup>  |
| HIC 150 | 1,0 m <sup>2</sup>  |
| HIC 180 | 12,1 m <sup>2</sup> |
| HIC 200 | 3,8 m <sup>2</sup>  |
| HIC 220 | 19,2 m <sup>2</sup> |

Data is subject to change without prior notice.

