

#### **Product technical sheet**

### **STEEL+ 1728**









4 - 14 years

44 kids

63,2 m<sup>2</sup>



#### **Material specification**

- $\bullet\,$  Powder galvanized and powder coated or stainless steel construction of 80 x 80 mm profile,
- Platforms and climbing walls made of durable anti-slip and waterproof HPL plate,
- Roofs and side panels made of durable HDPE plate, resistant to weather conditions,
- Transparent polycarbonate panels with a weather-resistant print,
- Slides made of stainless steel with durable HDPE side panels,
- Stainless steel tube slide,
- Drawing board made of durable HPL plate, resistant to weather conditions,
- Maze windows made of polycarbonate, balls made of synthetic material,
- Durable climbing stones made of polyester resin composite with mineral fillers,
- Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,
- Attested, safe seats,
- Calibrated stainless steel chains, preventing fingers entrapment,
- Stainless steel bars and handrails,
- Stainless steel screws and/or screws covered with plastic caps,
- Safe end caps on top of the structure made of rubber or polypropylene,



#### **Facilitating disability**



easy access



shelters



Intellectual development



manipulation

thinking



music



#### **Physical development**



balance



sliding



rest



passage



climbing

**Vinci Group Sp. z o.o.** Seminaryjna 9 Street 99-400 Łowicz VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26

M: +48 793 404 991












#### **Product technical sheet**


## **STEEL+ 1728**


## 7 number of interactive elements



6 number of activity elements







#### **Product data**

Length	825 cm	
Width	735 cm	
Total height	510 cm	
Age group	4 - 14 years	
Number of users	44 kids	
Safety zone	63,2 m2	
Free fall height	270 cm	
The height of the platforms	90, 120, 150, 180, 210, 240, 300 cm	
tube slide platform height	240 cm	
slide platform height	90, 120 cm	
In accordance with norm EN	1176-1:2017	
Weight of the heaviest part	235 kg	
Dimensions of the largest part 513x101x366 cm		
Availability of spare parts	YES	
Installation time	24 h	
Color options		

Data is subject to change without prior notice.

#### **Additional information**

- equipment adapted for the disabled; intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jamming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70 cm deep;
- slide should not be installed southwards;
- render is for reference only, the actual appearance of the equipment and its color may vary;

#### **Guarantee**



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card

**Vinci Group Sp. z o.o.** Seminaryjna 9 Street 99-400 Łowicz VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991





### Surfaces according to EN 1176-1:2017

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A,C)	Particle size from 20 to 80	30	≤200
		40	≤300
woodchips (A,C)	Particle size from 5 to 30	30	≤200
		40	≤300
sand or gravel (A,C)	Particle size from 0,25 to 8	30	≤200
		40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		270

#### **Product technical sheet**

## **STEEL+ 1728**

# Amount of safe surface corresponding with free fall height:

HIC 90	0,2 m <sup>2</sup>
HIC 100	22,3 m <sup>2</sup>
HIC 120	4,7 m <sup>2</sup>
HIC 150	5,2 m <sup>2</sup>
HIC 180	4,0 m <sup>2</sup>
HIC 240	4,1 m <sup>2</sup>
HIC 270	22,7 m <sup>2</sup>

Data is subject to change without prior notice.

