



# **Product technical sheet**

# **SWING ST0513**







3 - 12 years

7 kids

15,5 m<sup>2</sup>

# **Material specification**

- Stainless steel, hot-dip galvanized and powder coated or powder galvanized and powder coated steel construction of 100 x 100 mm profile,
- Colorful elements made of durable HDPE plate, resistant to weather conditions,
- Attested, safe seats,
- Calibrated stainless steel chains, preventing fingers entrapment,
- Stainless steel swing fittings,
- Screws covered with plastic caps and/or stainless steel screws,
- Safe end caps on the top of the bar, made of durable HDPE plate, resistant to weather conditions,



# **Facilitating disability**



easy access



integration



### **Physical development**







rocking







# 170



# **Product technical sheet**

# **SWING ST0513**

### **Product data**

Length	100 cm	
Width	290 cm	
Total height	170 cm	
Age group	3 - 12 years	
Number of users	7 kids	
Safety zone	15,5 m2	
Free fall height	105 cm	
In accordance with norm EN	1176-1:2017	
Weight of the heaviest part	22 kg	
Dimensions of the largest part	246x10x10 cm	
Availability of spare parts	YES	
Installation time	1 h	
Color options		

Data is subject to change without prior notice.

### **Additional information**

- equipment adapted for the disabled; intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- anchoring on flat surface, 100/90/80 cm deep;
- render is for reference only, the actual appearance of the equipment and its color may vary;

## **Guarantee**



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card





99-400 Łowicz

Seminaryjna 9 Street



# Surfaces according to EN 1176-1:2017

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A,C)  Particle size from 20 to 80	Particle size from 20	30	≤200
	to 80	40	≤300
woodchips (A,C)	Particle size from 5	30	≤200
	to 30	40	≤300
sand or gravel (A,C)	Particle size from 0,25 to 8	30	≤200
		40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		105

# **Product technical sheet**

# **SWING ST0513**

Amount of safe surface corresponding with free fall height:

HIC 105 15,5 m<sup>2</sup>

Data is subject to change without prior notice.

