## **Product technical sheet**

# **WORKOUT 2329**







14+

< 140 kg


129,1 m2


### **Product data**


Length	1137 cm	
Width	789 cm	
Total height	351 cm	
Age group	14+ years	
Maximum weight of user	140 kg	
Safety zone	129,1 m2	
Free fall height	249 cm	
In accordance with norm EN	16630:2015	
Weight of the heaviest part	38 kg	
Dimensions of the largest part	10x10x460 cm	
Availability of spare parts	YES	
Installation time	10 h	
Color options		

Data is subject to change without prior notice.

































**Vinci Group Sp. z o.o.** Seminaryjna 9 Street 99-400 Łowicz

VAT: 534-250-14-46

PHONE: +48 42 203 24 99 ext. 26

M: +48 793 404 991



biuro@vinci-play.com info@vinci-play.com www.vinci-play.com

### **Material specification**



Powder galvanized and powder-coated or stainless steel construction of 100 x 100 mm profile, dulrable end caps on the top of the structure made of plastic,



Aluminum exercise instructions plate screwed to HDPE plate, resistant to weather conditions,



Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,



Steel rope in polypropylene braid,



Seats/backrests made of durable HPL plate, resistant to weather conditions,



Stainless steel bars with a diameter of 38 mm for a comfortable grip during exercises.



Certified handles and calibrated chains made of stainless steel, preventing fingers from getting caught,



Stainless steel screws and/or screws covered with plastic caps,

#### Additional information

- equipment adapted for the disabled; device intended for public outdoor gyms;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- anchoring on flat surface, 100 cm deep;
- render is for reference only, the actual appearance of the equipment and its color may vary;

#### **Guarantee**

- 30 year guarantee Structural strength of steel and stainless steel components
- 15 year guarantee Structural failure of steel and stainless steel, for dynamic equipment
- 10 year guarantee Structural failure of high density polyethylene and high pressure laminates components
- 5 year guarantee Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card

Vinci Group Sp. z o.o. Seminaryjna 9 Street 99-400 Łowicz VAT: 534-250-14-46

PHONE: +48 42 203 24 99 ext. 26

M: +48 793 404 991



biuro@vinci-play.com info@vinci-play.com www.vinci-play.com


# Amount of safe surface corresponding with free fall height:

HIC <60	8,2 m <sup>2</sup>
HIC 72	9,6 m²
HIC 92	5,6 m <sup>2</sup>
HIC 112	5,9 m²
HIC 130	3,0 m <sup>2</sup>
HIC 141	14,0 m²
HIC 160	4,2 m²
HIC 180	15,4 m²
HIC 230	19,2 m²
HIC 249	44,0 m²

Data is subject to change without prior notice.

# **Surfaces according to EN 16630:2015**

	Description (mm)	Layer thickness (cm)	Maximum fall height (cm)
Concrete / stone / bituminous surfaces (A, B, C)	-	-	≤100
outer soil layer (A,B,C)	-	-	≤120
Turf (A,B,C)	-	-	≤150
bark (A,C)	Particle size from 20 to 80	30	≤200
		40	≤300
wood shavings/cuttings (A, C)	Particle size from 5 to 30	30	≤200
		40	≤300
sand (A,C)	Particle size from 0,2 to 2 mm	30	≤200
		40	≤300
gravel (A,C)	Particle size from 2 to 8	30	≤200
		40	≤300
attested synthetic (A, B, C)	Tested according to EN 1177		249





biuro@vinci-play.com info@vinci-play.com www.vinci-play.com