Product technical sheet

WORKOUT RB2325




Product data

Length	494 cm	
Width	464 cm	
Total height	347 cm	
Age group	14+ years	
Maximum weight of user	140 kg	
Safety zone	52,3 m2	
Free fall height	245 cm	
In accordance with norm EN	16630:2015	
Weight of the heaviest part	96 kg	
Dimensions of the largest part	4x4x450 cm	
Availability of spare parts	YES	
Installation time	6 h	

Data is subject to change without prior notice.





HIC < 60 5,3 m²

HIC 92 2,4 m² ~

HIC 123 0,2 m²

🕲 52,3 m²







Vinci Group Sp. z o.o. Seminaryjna 9 Street 99-400 Łowicz VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991



biuro@vinci-play.com info@vinci-play.com www.vinci-play.com

22/07/2022

1/3


Material specification





Construction made of Robinia - verv durable acacia wood with a diameter of ~ 18 cm without sharp edges, resistant to weather conditions,

Aluminum exercise instructions plate screwed to HDPE plate, resistant to weather conditions,



Seats/backrests made of durable HPL plate, resistant to weather conditions,

Stainless steel bars with a diameter of 38 mm for a comfortable grip during exercises.




- equipment adapted for the disabled; device intended for public outdoor gyms;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- anchoring on flat surface, 100 cm deep;
- render is for reference only, the actual appearance of the equipment and its color may vary;

Guarantee


30 year guarantee - Structural strength of steel and stainless steel components

Stainless steel bars and handrails,





Stainless steel screws and/or screws covered with plastic caps,



30 15

15 year guarantee - Structural failure of steel and stainless steel, for dynamic equipment



5

10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components

5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card

Vinci Group Sp. z o.o. Seminaryjna 9 Street 99-400 Łowicz

VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991



biuro@vinci-play.com info@vinci-play.com www.vinci-play.com

Amount of safe surface corresponding with free fall height:

HIC <60	5,3 m ²
HIC 92	2,4 m ²
HIC 112	4,4 m ²
HIC 123	0,2 m ²
HIC 226	9,0 m ²
HIC 245	31,0 m ²


Data is subject to change without prior notice.


Surfaces according to EN 16630:2015

	Description (mm)	Layer thickness (cm)	Maximum fall height (cm)
Concrete / stone / bituminous surfaces (A, B, C)	-	-	≤100
outer soil layer (A,B,C)	-	-	≤120
Turf (A,B,C)	-	-	≤150
bark (A,C)	Particle size from 20 to 80	30	≤200
		40	≤300
wood shavings/cuttings (A, C)	Particle size from 5 to 30	30	≤200
		40	≤300
sand (A,C)	Particle size from 0,2 to 2 mm	30	≤200
		40	≤300
gravel (A,C)	Particle size from 2 to 8	30	≤200
		40	≤300
attested synthetic (A, B, C)	Tested according to EN 1177		245

A

B





С

wôrkôut

20

biuro@vinci-play.com info@vinci-play.com www.vinci-play.com

Vinci Group Sp. z o.o. Seminaryjna 9 Street 99-400 Łowicz VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991

22/07/2022