



Product technical sheet

CROOC 0305







3 - 12 years

15 kids

30,3 m²



Material specification

- Stainless steel structure of 80 x 80 mm profile,
- Roofs and side panels and seats made of durable HPL plate, resistant to weather
- Slides made of stainless steel with durable HPL side panels,
- Educational paneles and moving elements made of HPL plate, resistant to weather conditions,
- Stainless steel bars,
- Screws covered with plastic caps and/or stainless steel screws,
- Safe end caps on top of the structure made of rubber or polypropylene,



Facilitating disability



easy access



shelters



integration



Intellectual development



manipulation



thinking



Physical development



hiding climbing



sliding










Product technical sheet


CROOC 0305






number of activity elements







Product data

| Length | 324 cm | |
|--------------------------------|--------------|--|
| Width | 292 cm | |
| Total height | 250 cm | |
| Age group | 3 - 12 years | |
| Number of users | 15 kids | |
| Safety zone | 30,3 m2 | |
| Free fall height | 90 cm | |
| The height of the platforms | 59, 90 cm | |
| In accordance with norm EN | 1176-1:2017 | |
| Weight of the heaviest part | 38 kg | |
| Dimensions of the largest part | 305x8x8 cm | |
| Availability of spare parts | YES | |
| Installation time | 6,5 h | |
| Color options | | |

Data is subject to change without prior notice.

Additional information

- equipment adapted for the disabled; intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- slide should not be installed southwards;
- render is for reference only, the actual appearance of the equipment and its color may vary;

Guarantee



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card

Vinci Group Sp. z o.o. Seminaryjna 9 Street 99-400 Łowicz VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991



biuro@vinci-play.com info@vinci-play.com www.vinci-play.com



Surfaces according to EN 1176-1:2017

| | Description (mm) | Layer thickness (cm) | Maximum fall heights (cm) |
|---|---------------------------------|-------------------------|------------------------------|
| Turf/ top layer of soil (A,B,C) | - | - | ≤100 |
| bark (A,C) | Particle size from 20 | 30 | ≤200 |
| | to 80 | 40 | ≤300 |
| woodchips (A,C) Particle size from 5 to 30 | Particle size from 5 | 30 | ≤200 |
| | to 30 | 40 | ≤300 |
| sand or gravel (A,C) | Particle size from 0,25 to 8 | 30 | ≤200 |
| | | 40 | ≤300 |
| synthetic attested (A,B,C) | d Tested according to EN 1177 | | 100 |

Product technical sheet

CROOC 0305

Amount of safe surface corresponding with free fall height:

| HIC <60 | 3,7 m ² |
|---------|--------------------|
| HIC 90 | 12,2 m² |
| HIC 100 | 14,4 m² |

Data is subject to change without prior notice.

