



#### **Product technical sheet**

### **JUNGLE 3227**







4 - 14 years

38 kids

43,1 m<sup>2</sup>



#### **Material specification**

- $\bullet\,$  Powder galvanized and powder coated or stainless steel construction of 80 x 80 mm profile,
- Platforms and climbing walls made of durable anti-slip and waterproof HPL plate,
- Roofs and side panels made of durable HDPE plate, resistant to weather conditions,
- Transparent polycarbonate panels with a weather-resistant print,
- Slides made of stainless steel with durable HDPE side panels,
- Drawing board made of durable HPL plate, resistant to weather conditions,
- Maze windows made of polycarbonate, balls made of synthetic material,
- Durable climbing stones made of polyester resin composite with mineral fillers,
- Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,
- Attested, safe seats,
- Calibrated stainless steel chains, preventing fingers entrapment,
- Stainless steel bars, ladders and handrails,
- Stainless steel screws and/or screws covered with plastic caps,
- Safe end caps on top of the structure made of rubber or polypropylene,



#### Facilitating disability



easy access

integration



shelters



#### Intellectual development



manipulation



thinking



#### **Physical development**



hiding



sliding



rest



climbing













# Product technical sheet JUNGLE 3227






4 number of activity elements







#### **Product data**

| Length                                    | 535 cm                                 |  |
|---|--|--|
| Width                                     | 375 cm                                 |  |
| Total height                              | 510 cm                                 |  |
| Age group                                 | 4 - 14 years                           |  |
| Number of users                           | 38 kids                                |  |
| Safety zone                               | 43,1 m2                                |  |
| Free fall height                          | 270 cm                                 |  |
| The height of the platforms               | 90, 120, 150, 180, 210,<br>240, 300 cm |  |
| slide platform height                     | 90, 210 cm                             |  |
| In accordance with norm EN                | 1176-1:2017                            |  |
| Weight of the heaviest part               | 65 kg                                  |  |
| Dimensions of the largest part 8x8x510 cm |  |  |
| Availability of spare parts               | YES                                    |  |
| Installation time                         | 8,5 h                                  |  |
| Color options                             | 60                                     |  |

Data is subject to change without prior notice.

#### **Additional information**

- equipment adapted for the disabled; intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70 cm deep;
- slide should not be installed southwards;
- render is for reference only, the actual appearance of the equipment and its color may vary;

#### Guarantee



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card

**Vinci Group Sp. z o.o.** Seminaryjna 9 Street 99-400 Łowicz VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991





### Surfaces according to EN 1176-1:2017

|                                 | Description (mm)                | Layer thickness<br>(cm) | Maximum fall<br>heights (cm) |
|---------------------------------|---------------------------------|-------------------------|------------------------------|
| Turf/ top layer of soil (A,B,C) | -                               | -                       | ≤100                         |
| bark (A,C)                      | Particle size from 20<br>to 80  | 30                      | ≤200                         |
|                                 |                                 | 40                      | ≤300                         |
| woodchips (A,C)                 | Particle size from 5<br>to 30   | 30                      | ≤200                         |
|                                 |                                 | 40                      | ≤300                         |
| sand or gravel (A,C)            | Particle size from<br>0,25 to 8 | 30                      | ≤200                         |
|                                 |                                 | 40                      | ≤300                         |
| synthetic attested (A,B,C)      | Tested according to EN 1177     |                         | 270                          |

#### **Product technical sheet**

## **JUNGLE 3227**

# Amount of safe surface corresponding with free fall height:

| HIC <60 | 0,1 m <sup>2</sup>  |
|---------|---------------------|
| HIC 90  | 0,1 m <sup>2</sup>  |
| HIC 100 | 11,0 m <sup>2</sup> |
| HIC 120 | 0,1 m <sup>2</sup>  |
| HIC 210 | 5,3 m <sup>2</sup>  |
| HIC 240 | 3,8 m <sup>2</sup>  |
| HIC 270 | 22,7 m <sup>2</sup> |

Data is subject to change without prior notice.

