

#### **Product technical sheet**

## **RECYCLED RC0499**







3 - 14 years

4 years 4

4 kids

19,2 m<sup>2</sup>



#### **Material specification**

- The structure is made of a durable, moisture-resistant and low-temperature recycled composite,
- Climbing walls made of durable anti-slip and waterproof plywood or HPL plate,
- Climbing stones made of green HDPE plates made of 100% recycled material, e.g. ocean waste such as fishing nets and ropes, resistant to weather conditions,
- Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,
- Stainless steel screws and/or screws covered with plastic caps,



**Physical development** 




climbing

















#### **Product technical sheet**

### **RECYCLED RC0499**

#### **Product data**

Length	135 cm	
Width	185 cm	
Total height	45 cm	
Age group	3 - 14 years	
Number of users	4 kids	
Safety zone	19,2 m2	
Free fall height	<60 cm	
In accordance with norm EN	1176-1:2017	
Weight of the heaviest part	29 kg	
Dimensions of the largest part	180x71x4 cm	
Availability of spare parts	YES	
Installation time 2 h		

Data is subject to change without prior notice.

#### **Additional information**

- equipment intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jamming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- render is for reference only, the actual appearance of the equipment and its color may vary;

#### **Guarantee**



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card



VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991





### Surfaces according to EN 1176-1:2017

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
hark (A.C.)	Particle size from 20 to 80 40	≤200	
bark (A,C)		40	≤300
woodchips (A,C)	Particle size from 5 to 30	30	≤200
		40	≤300
sand or gravel (A,C)	Particle size from 0,25 to 8	30	≤200
		40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		<60

#### **Product technical sheet**

# **RECYCLED RC0499**

Amount of safe surface corresponding with free fall height:

HIC <60 19,2 m<sup>2</sup>

Data is subject to change without prior notice.

