

### **Product technical sheet**

# **RECYCLED RC0670**







1 - 12 years

4 kids

18,8 m<sup>2</sup>



## **Material specification**

- Hot-dip galvanized and powder coated or powder galvanized and powder coated steel construction elements,
- Structural elements made of recycled HDPE board, resistant to weather conditions,
- Seats made of recycled HDPE board, resistant to weather conditions,
- Handles made of synthetic material,
- Footrests made of synthetic material,
- Steel springs 20 mm, iron phosphorated and powder coated,
- Screws covered with plastic caps and/or stainless steel screws,



**Physical development** 





rocking











### **Product technical sheet**

# **RECYCLED RC0670**

### **Product data**

333 cm	
25 cm	
85 cm	
1 - 12 years	
4 kids	
18,8 m2	
<60 cm	
1176-1:2017	
19 kg	
6x8x333 cm	
YES	
1,5 h	

Data is subject to change without prior notice.

### **Additional information**

- equipment intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- render is for reference only, the actual appearance of the equipment and its color may vary;

### **Guarantee**



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card



VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991



99-400 Łowicz

Seminaryjna 9 Street



# Surfaces according to EN 1176-1:2017

4

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A,C)	Particle size from 20 to 80	30	≤200
		40	≤300
woodchips (A,C)	Particle size from 5 to 30	30	≤200
		40	≤300
sand or gravel (A,C)	Particle size from	30	≤200
	0,25 to 8	40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		60

# B C

## **Product technical sheet**

# **RECYCLED RC0670**

Amount of safe surface corresponding with free fall height:

HIC <60 18,8 m<sup>2</sup>

Data is subject to change without prior notice.

