

Product technical sheet

RECYCLED RC0825







3 - 12 years

20 kids

38,6 m²



Material specification

- Hot-dip galvanized and powder coated or powder galvanized and powder coated steel construction,
- Platforms made of durable anti-slip and waterproof plywood or HPL plate,
- Roofs and side panels made of recycled HDPE plates, resistant to weather conditions, green HDPE panels made of 100% recycled materials, e.g. ocean waste such as fishing nets and ropes
- Double wall tube passage made of polypropylene,
- Stainless steel bars,
- Handles made of recycled HDPE plates, resistant to weather conditions,
- Stainless steel screws and/or screws covered with plastic caps,



Physical development



hiding climbing



rest



crawling


Vinci Group Sp. z o.o. Seminaryjna 9 Street 99-400 Łowicz VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991

















Product technical sheet

RECYCLED RC0825

Product data

Length	734 cm	
Width	94 cm	
Total height	166 cm	
Age group	3 - 12 years	
Number of users	20 kids	
Safety zone	38,6 m2	
Free fall height	90 cm	
The height of the platforms	10 cm	
In accordance with norm EN	1176-1:2017	
Weight of the heaviest part	36 kg	
Dimensions of the largest part	251x82x78 cm	
Availability of spare parts	YES	
Installation time	9,0 h	

Data is subject to change without prior notice.

Additional information

- equipment intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jamming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- render is for reference only, the actual appearance of the equipment and its color may vary;

Guarantee



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card



VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991





Surfaces according to EN 1176-1:2017

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A,C) Particle size from 20 to 80	30	≤200	
	to 80	40	≤300
woodchips (A,C) Particle size from 5 to 30	Particle size from 5	30	≤200
	to 30	40	≤300
sand or gravel (A,C)	Particle size from 0,25 to 8	30	≤200
		40	≤300
synthetic attested (A,B,C)	d Tested according to EN 1177		90

Product technical sheet

RECYCLED RC0825

Amount of safe surface corresponding with free fall height:

HIC <60	23,8 m ²
HIC 90	14,8 m²

Data is subject to change without prior notice.

