



Product technical sheet

RECYCLED RC1443







3 - 14 years

3 kids

19.5 m²

Material specification

- The structure is made of a durable, moisture-resistant and low-temperature recycled composite,
- Platforms made of durable anti-slip and waterproof plywood or HPL plate,
- The covers are made of recycled HDPE panel, resistant to weather conditions
- Slides made of stainless steel with sides made of recycled HDPE boards, resistant to atmospheric conditions,
- Stainless steel bars,
- Stainless steel screws and/or screws covered with plastic caps,



Physical development




sliding





climbing











Product technical sheet

RECYCLED RC1443

Product data

| Length | 285 cm | |
|--------------------------------|--------------|--|
| Width | 84 cm | |
| Total height | 231 cm | |
| Age group | 3 - 14 years | |
| Number of users | 3 kids | |
| Safety zone | 19.5 m2 | |
| Free fall height | <60 cm | |
| The height of the platforms | 35 cm | |
| In accordance with norm EN | 1176-1:2017 | |
| Weight of the heaviest part | 40 kg | |
| Dimensions of the largest part | 262x52x15 cm | |
| Availability of spare parts | YES | |
| Installation time | 3 h | |
| | | |

Data is subject to change without prior notice.

Additional information

- equipment intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jamming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- slide should not be installed southwards;
- render is for reference only, the actual appearance of the equipment and its color may vary;

Guarantee



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card

Vinci Group Sp. z o.o. Seminaryjna 9 Street 99-400 Łowicz VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991





Surfaces according to EN 1176-1:2017

| | Description (mm) | Layer thickness (cm) | Maximum fall heights (cm) |
|---------------------------------|---------------------------------|-------------------------|------------------------------|
| Turf/ top layer of soil (A,B,C) | - | - | ≤100 |
| bark (A,C) | Particle size from 20 | 30 | ≤200 |
| | to 80 | 40 | ≤300 |
| woodchine (A C) | Particle size from 5 | 30 | ≤200 |
| | to 30 | 40 | ≤300 |
| sand or gravel (A,C) | Particle size from 0,25 to 8 | 30 | ≤200 |
| | | 40 | ≤300 |
| synthetic attested (A,B,C) | Tested according to EN 1177 | | 100 |

Product technical sheet

RECYCLED RC1443

Amount of safe surface corresponding with free fall height:

| HIC <60 | 9,6 m ² |
|---------|--------------------|
| HIC 100 | 9,9 m² |

Data is subject to change without prior notice.

