

Product technical sheet

RECYCLED RC1455







1 - 12 years

ears 23 kids

28,6 m²





- The structure is made of a durable, moisture-resistant and low-temperature recycled composite,
- Stainless steel construction,
- Platforms made of durable anti-slip and waterproof plywood or HPL plate,
- Structure for platforms made of hot-dip galvanized and powder coated steel;
- Roofs and side panels made of recycled HDPE plates, resistant to weather conditions, green HDPE panels made of 100% recycled materials, e.g. ocean waste such as fishing nets and ropes
- Elements made from recycled HDPE plates, resistant to weather conditions,
- Manipulative panels made of recycled HDPE plates, resistant to weather conditions, green HDPE panels made of 100% recycled, e.g. ocean waste such as fishing nets and ropes,
- Drawing board made of durable, waterproof plywood or HPL plate, resistant to weather conditions,
- Stainless steel bars,
- Screws covered with plastic caps and/or stainless steel screws,



Facilitating disability



easy access



integration



Intellectual development



manipulation

thinking



sensorics



Physical development



rest









Product technical sheet

RECYCLED RC1455


Product data


Length	348 cm	
Width	171 cm	
Total height	191 cm	
Age group	1 - 12 years	
Number of users	23 kids	
Safety zone	28,6 m2	
Free fall height	<60 cm	
The height of the platforms	35 cm	
In accordance with norm EN	1176-1:2017	
Weight of the heaviest part	12 kg	
Dimensions of the largest part	249x9x9 cm	
Availability of spare parts	YES	
Installation time	5 h	

Data is subject to change without prior notice.

Additional information

- equipment adapted for the disabled; intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jamming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- render is for reference only, the actual appearance of the equipment and its color may vary;







Guarantee



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card



VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991





Surfaces according to EN 1176-1:2017

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A.C.)	A,C) Particle size from 20 to 80 40	30	≤200
bark (A,C)		40	≤300
woodchips (A,C)	Particle size from 5 to 30	30	≤200
		40	≤300
sand or gravel (A,C)	Particle size from 0,25 to 8	30	≤200
		40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		60

Product technical sheet

RECYCLED RC1455

Amount of safe surface corresponding with free fall height:

HIC <60 28,6 m²

Data is subject to change without prior notice.

