



Product technical sheet

RECYCLED RC1461







3 - 14 years

28 kids

44,7 m²



Material specification

- The structure is made of a durable, moisture-resistant and low-temperature recycled composite,
- Platforms made of durable anti-slip and waterproof plywood or HPL plate,
- The covers are made of recycled HDPE panel, resistant to weather conditions
- Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,
- Steel springs 20 mm, iron phosphorated and powder coated,
- Stainless steel bars and handrails,
- Screws covered with plastic caps and/or stainless steel screws,
- Safe end caps made of polypropylene,



Physical development



balance passage



pull-up


Vinci Group Sp. z o.o. Seminaryjna 9 Street 99-400 Łowicz


VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991














Product technical sheet

RECYCLED RC1461

Product data

Length	535 cm	
Width	306 cm	
Total height	140 cm	
Age group	3 - 14 years	
Number of users	28 kids	
Safety zone	44,7 m2	
Free fall height	< 60 cm	
The height of the platforms	29, 59 cm	
In accordance with norm EN	1176-1:2017	
Weight of the heaviest part	24 kg	
Dimensions of the largest part	159x46x17 cm	
Availability of spare parts	YES	
Installation time	13 h	

Data is subject to change without prior notice.

Additional information

- equipment intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- render is for reference only, the actual appearance of the equipment and its color may vary;

Guarantee



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card



VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991





Surfaces according to EN 1176-1:2017

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A.C.)	Particle size from 20 to 80 40	≤200	
bark (A,C)		40	≤300
woodchips (A,C) Particle size from 5 to 30	30	≤200	
	to 30	40	≤300
sand or gravel (A,C) Particle size from 0,25 to 8	Particle size from	30	≤200
	0,25 to 8	40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		< 60

Product technical sheet

RECYCLED RC1461

Amount of safe surface corresponding with free fall height:

HIC <60 44,7 m²

Data is subject to change without prior notice.

