



Product technical sheet

SWING ST0519



3 - 14 years



3 kids



52,8 m²

R1



R3



R18



Material specification

- Hot-dip galvanized and powder coated or powder galvanized and powder coated steel construction,
- Attested, safe seats,
- Calibrated stainless steel chains, preventing fingers entrapment,
- Stainless steel swing fittings,
- Stainless steel screws and/or screws covered with plastic caps,



Physical development




spinning



rocking





Product technical sheet

SWING ST0519

Product data

Length	221 cm
Width	199 cm
Total height	242 cm
Age group	3 - 14 years
Number of users	3 kids
Safety zone	52,8 m²
Free fall height	130 cm
In accordance with norm EN	1176-1:2017
Weight of the heaviest part	31 kg
Dimensions of the largest part	309x11x11 cm
Availability of spare parts	YES
Installation time	1 h
Color options	

Data is subject to change without prior notice.

Additional information

- equipment intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- available types of seats in the swing: R1-flat, R2-basket, R3-flat belt, R5-flat with barrier;
- no sharp edges or chinks that would pose a danger of jimmie the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- render is for reference only, the actual appearance of the equipment and its color may vary;

Guarantee

30	30 year guarantee - Structural strength of steel and stainless steel components	15	15 year guarantee - Structural failure of steel and stainless steel, for dynamic equipment	10	10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components	5	5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements
-----------	---	-----------	--	-----------	--	----------	---

Detailed information in the guarantee card



Surfaces according to EN 1176-1:2017

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A,C)	Particle size from 20 to 80	30	≤200
		40	≤300
woodchips (A,C)	Particle size from 5 to 30	30	≤200
		40	≤300
sand or gravel (A,C)	Particle size from 0,25 to 8	30	≤200
		40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		130

Product technical sheet

SWING ST0519

Amount of safe surface corresponding with free fall height:

HIC 130 52,8 m²

Data is subject to change without prior notice.

