



Product technical sheet

SWING WD1423-1







3 - 12 years

7 kids

18,1 m²

Material specification

- Construction made of the highest quality laminated, impregnated and double coated pine wood 90 x 90 mm without knots, secured from the top with polypropylene plugs.
- Metal anchors made of hot dip galvanized steel, protecting the wood from direct contact with the ground to prevent rot and to extend the product's life,
- Hot-dip galvanized and powder coated or powder galvanized and powder coated or stainless steel construction elements,
- Attested, safe seats,
- Calibrated stainless steel chains, preventing fingers entrapment,
- Stainless steel swing fittings,
- Stainless steel screws and/or screws covered with plastic caps,



Facilitating disability



easy access



integration



Physical development




rest




rocking





240



Product technical sheet

SWING WD1423-1

Product data

Length	195 cm	
Width	320 cm	
Total height	240 cm	
Age group	3 - 12 years	
Number of users	7 kids	
Safety zone	18,1 m2	
Free fall height	130 cm	
In accordance with norm EN	1176-1:2017	
Weight of the heaviest part	17 kg	
Dimensions of the largest part 237x9x9 cm		
Availability of spare parts	YES	
Installation time	2 h	
Color options		

Data is subject to change without prior notice.

Additional information

- equipment adapted for the disabled; intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jamming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- render is for reference only, the actual appearance of the equipment and its color may vary;

Guarantee



30 year guarantee -Structural strength of steel 15 and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card





Surfaces according to EN 1176-1:2017

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A.C.)	Particle size from 20 to 80	30	≤200
bark (A,C)		40	≤300
woodchips (A,C) Particle size fr to 30	Particle size from 5	30	≤200
	to 30	40	≤300
sand or gravel (A,C)	Particle size from	30	≤200
	0,25 to 8	40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		130

B C

Product technical sheet

SWING WD1423-1

Amount of safe surface corresponding with free fall height:

HIC 130 18,1 m²

Data is subject to change without prior notice.