

Product technical sheet

WOODEN WD1452







7 - 16 years

31 kids

47,8 m²





Material specification

- Construction made of the highest quality laminated, impregnated and double coated pine wood 90 x 90 mm without knots, secured from the top with polypropylene plugs,
- Metal anchors made of hot dip galvanized steel, protecting the wood from direct contact with the ground to prevent rot and to extend the product's life,
- Platforms made of durable anti-slip and waterproof plywood or HPL plate,
- Structure for platforms made of hot-dip galvanized and powder coated steel;
- Side panels made of durable HDPE or HPL plate, resistant to weather conditions,
- Tubular sled made of stainless steel,
- Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,
- Ladders made of steel ropes in polypropylene braid and rungs made of synthetic material,
- Handles made of synthetic material,
- Stainless steel bars, ladders and handrails,
- Screws covered with plastic caps and/or stainless steel screws,
- Safe end caps made of polypropylene,



Physical development



balance

pull-up

climbing



sliding



passage

Vinci Group Sp. z o.o. Seminaryjna 9 Street 99-400 Łowicz


VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991

















Product technical sheet

WOODEN WD1452

Product data

| Length | 528 cm | |
|--------------------------------|--------------|--|
| Width | 428 cm | |
| Total height | 260 cm | |
| Age group | 7 - 16 years | |
| Number of users | 31 kids | |
| Safety zone | 47,8 m2 | |
| Free fall height | 250 cm | |
| The height of the platforms | 150, 180 cm | |
| In accordance with norm EN | 1176-1:2017 | |
| Weight of the heaviest part | 11 kg | |
| Dimensions of the largest part | 249x9x9 cm | |
| Availability of spare parts | YES | |
| Installation time | 9 h | |
| Color options | | |

Data is subject to change without prior notice.

Additional information

- equipment intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- render is for reference only, the actual appearance of the equipment and its color may vary;

Guarantee



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card



VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991





Surfaces according to EN 1176-1:2017

| | Description (mm) | Layer thickness (cm) | Maximum fall heights (cm) |
|---|---------------------------------|-------------------------|------------------------------|
| Turf/ top layer of soil (A,B,C) | - | - | ≤100 |
| bark (A,C) Particle size from 20 to 80 | 30 | ≤200 | |
| | to 80 | 40 | ≤300 |
| woodchips (A,C) Particle size from 5 to 30 | 30 | ≤200 | |
| | to 30 | 40 | ≤300 |
| sand or gravel (A,C) | Particle size from 0,25 to 8 | 30 | ≤200 |
| | | 40 | ≤300 |
| synthetic attested (A,B,C) | Tested according to EN 1177 | | 250 |

Product technical sheet

WOODEN WD1452

Amount of safe surface corresponding with free fall height:

| HIC 150 | 5,3 m ² |
|---------|---------------------|
| HIC 180 | 2,2 m ² |
| HIC 200 | 14,2 m² |
| HIC 250 | 26,1 m ² |

Data is subject to change without prior notice.

