

## Product technical sheet

# WORKOUT 2318



14+



< 140 kg





10,1 m<sup>2</sup>

### Product data

|                                |                     |
|--------------------------------|---------------------|
| Length                         | 55 cm               |
| Width                          | 40 cm               |
| Total height                   | 20 cm               |
| Age group                      | 14+ years           |
| Maximum weight of user         | 140 kg              |
| Safety zone                    | 10,1 m <sup>2</sup> |
| Free fall height               | < 60 cm             |
| In accordance with norm EN     | 16630:2015          |
| Weight of the heaviest part    | 1 kg                |
| Dimensions of the largest part | 20x50x1 cm          |
| Availability of spare parts    | YES                 |
| Installation time              | 2 h                 |
| Color options                  |                     |

Data is subject to change without prior notice.



**Vinci Group Sp. z o.o.**  
Seminaryjna 9 Street  
99-400 Łowicz

VAT: 534-250-14-46  
PHONE: +48 42 203 24 99 ext. 26  
M: +48 793 404 991

02/04/2024

**workout**


biuro@vinci-play.com  
info@vinci-play.com  
[www.vinci-play.com](http://www.vinci-play.com)

1 / 3

## Material specification



Platforms made of durable anti-slip and waterproof HPL plate,



Stainless steel screws and/or screws covered with plastic caps,

## Additional information

- device intended for public outdoor gyms;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimmie the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- render is for reference only, the actual appearance of the equipment and its color may vary;

## Guarantee

- 30** 30 year guarantee - Structural strength of steel and stainless steel components
- 15** 15 year guarantee - Structural failure of steel and stainless steel, for dynamic equipment
- 10** 10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components
- 5** 5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements


Detailed information in the guarantee card

# Amount of safe surface corresponding with free fall height:

|                                                 |                     |
|-------------------------------------------------|---------------------|
| HIC <60                                         | 10,1 m <sup>2</sup> |
| Data is subject to change without prior notice. |                     |

# Surfaces according to EN 16630:2015

|                                                  | Description (mm)               | Layer thickness (cm) | Maximum fall height (cm) |
|--------------------------------------------------|--------------------------------|----------------------|--------------------------|
| Concrete / stone / bituminous surfaces (A, B, C) | -                              | -                    | ≤100                     |
| outer soil layer (A,B,C)                         | -                              | -                    | ≤120                     |
| Turf (A,B,C)                                     | -                              | -                    | ≤150                     |
| bark (A,C)                                       | Particle size from 20 to 80    | 30                   | ≤200                     |
|                                                  |                                | 40                   | ≤300                     |
| wood shavings/cuttings (A, C)                    | Particle size from 5 to 30     | 30                   | ≤200                     |
|                                                  |                                | 40                   | ≤300                     |
| sand (A,C)                                       | Particle size from 0,2 to 2 mm | 30                   | ≤200                     |
|                                                  |                                | 40                   | ≤300                     |
| gravel (A,C)                                     | Particle size from 2 to 8      | 30                   | ≤200                     |
|                                                  |                                | 40                   | ≤300                     |
| attested synthetic (A, B, C)                     | Tested according to EN 1177    |                      | < 60                     |



Vinci Group Sp. z o.o.  
 Seminaryjna 9 Street  
 99-400 Łowicz

VAT: 534-250-14-46  
 PHONE: +48 42 203 24 99 ext. 26  
 M: +48 793 404 991